

## Rinnai Q Series

Designed for Australia's ever-changing climate, the Rinnai Q Series Inverter Split System provides both cooling and heating all year round no matter where you live.

Packed with innovative features including Wi-Fi connectivity, self-cleaning function and sleep mode, the Q Series is the ultimate in providing complete comfort. This smart system can also work around your unique lifestyle with an ultra-practical timer function, allowing you to set the unit's operation times to achieve the perfect room temperature.





# Performance to keep you comfortable





#### **Ambient Temperature**

The Rinnai Q Series will continue to perform with reliable operation even in extreme weather. Our units can work in ambient winter temperatures as low as -15°C and ambient summer temperatures as high as 52°C, an essential feature for the harsh climate conditions across Australia.

#### **Intelligent Defrosting**

In areas with low ambient temperature where the outdoor temperature may fall below freezing, the outdoor unit will run in anti-frost mode and ensure high performance heating.

#### **Long Distance Air Supply**

The Q Series will supply volumes of cool air with airflow distances reaching up to 15 metres, creating a comfortable environment wall to wall.

#### **Self-Diagnosis Function**

In the unlikely event that there is abnormal operation, the system will switch off automatically, determine what is at fault and display an error code on the indoor unit.

## **Features and Benefits**







#### Wi-Fi Control

Set your favourite temperature from anywhere, with our intuitive Android or Apple App.
Come home to ultimate comfort.



#### **Self-Cleaning Function**

End of season cleaning process dries the inside of the unit, ensuring its free from mold, bacteria and dust during extended periods of non-use.



#### **Quiet Operation**

Designed to keep noise levels to a minimum without affecting performance, thanks to a cleverly designed air tunnel optimised to deliver better air distribution.



#### 3D Airflow

Air blades can be controlled to swing both horizontally and vertically, allowing for balanced room temperature and comfort.



#### **Turbo Function**

Quickly cool in summer or swiftly warm in winter.



#### Sleep Mode

The Q Series intelligent sleep mode operates on a two-way temperature control that modulates up and down to mimic outside ambient temperatures, ensuring a comfortable sleep.



#### **Timer**

A delay ON or OFF timer allows you to select a period of time (from 30 minutes to 24 hours), the unit will turn either on or off depending on its current status.



#### **Programmable Timer**

7-day programmable timer can be operated via an iOS or Android Wi-Fi App for added functionality and control.



#### **Fresh Function**

Every time the unit is turned off, a 3 minute cleaning cycle is ran, keeping the indoor unit free of excess moisture. This helps extend life of the unit whilst ensuring optimum performance and hygiene.



#### **R32 Refrigerant**

R32 refrigerant has lower global warming potential than traditional refrigerants. Also provides higher energy efficiency while using lower refrigerant volumes.



#### **Demand Control**

Equipped with demand response capability (DRED) to help reduce overall power consumption at critical peak load times\*\*

<sup>\*</sup>For full terms & conditions visit www.rinnai.com.au

<sup>\*\*</sup>Subject to availability from your energy provider.

## Comfort at the touch of a button



set your temperature, fan speed and more remotely from anywhere in the world with an Internet connection.


Turn your Air Conditioner on or off,



Your home's Internet router relays requests from the App to control your Air Conditioner just like the normal remote controller.



Set your favourite temperature before you come home - enjoy the comfort and energy savings.



- · Google Play
- App Store



# **Technical Information**

Nominal Capacity

Nominal Capacity		kW	2.5	3.5	5.0	7.0	8.0	
Power Supply to Outdoor Unit		V-ph-Hz			220~240 - 1 - 50			
Recommended Circuit Beaker		А	16	16	16	20	25	
Connectivity		-	- Wi-Fi Enabled					
Demand Response Enabling Device		-	- DRED Enabled					
Cooling	Rated Capacity	kW	2.5	3.4	5.2	7.0	8.0	
	Capacity Range		0.8~3.3	0.8~4.2	0.85~6.4	0.95~7.8	1.30 ~ 8.50	
	Rated Power Input	W	525	740	1200	1865	2400	
	Rated Current (Range)	Α	2.3 (0.9 ~ 6.0)	3.3 (0.9 ~ 6.5)	5.2 (1.5 ~ 8.1)	8.1 (1.5 ~ 11.5)	11.0 (3.1 ~ 18.0)	
	AEER	W/W	4.805	4.841	4.432	3.801	3.310	
	Star Rating	-	5.0	5.0	4.0	3.0	2.0	
Heating	Rated Capacity	kW	2.5	3.5	5.2	7.0	8.4	
	Capacity Range		0.8 ~ 3.4	0.8~4.2	0.9~6.5	0.85~8.0	2.6~8.8	
	Rated Power Input	W	525	740	1210	1850	2550	
	Rated Current (Range)	А	2.3 (0.7 ~ 5.2)	3.3 (0.9 ~ 6.0)	5.3 (1.4 ~ 8.0)	8.0 (1.5 ~ 11.5)	11.0 (2.6 ~ 17.0)	
	ACOP	W/W	4.905	4.864	4.422	3.868	3.270	
	Star Rating	_	5.0	5.0	4.0	3.0	2.0	
Maximum Input Powe	er (Cooling / Heating)	W	1340 /1340	1460 / 1460	2000/2000	2500/2500	3000/3000	
Maximum Input Current (Cooling / Heating)		A	6.0 / 6.0	6.5 / 6.5	9.0/9.0	11.5 / 11.5	18.0/18.0	
Suitable Area Coverage (up to 2.6m insulated ceiling)		m²	13~22	18~30	27~45	37~61	42~70	
Cartable / troat Covere	igo (ap to 2.011111ballatoa ooliili ig)	111	10 22	10 00	21 10	01 01	12 70	
Air Flow (Turbo / Hi / Med / Lo / Silent)		L/s	194 / 176 / 147 / 115 / 105	305 / 255 / 197 / 152 / 138	333/291/243/ 186/156	361/327/258/ 198/169	372/323/276/ 230/180	
Sound Pressure @ 1.4m		.=	43/39/35/	50/45/41/	50/47/42/	50/47/42/	50/46/43/	
(Turbo/Hi/Med/Lo/Silent)		dB(A)	31/25	35/26	36/27	36/27	37/27	
Air Swing Louvres		Direction			Horizontal & Vertical			
Dimensions	Dimension (WxHxD)	mm	850 × 300 × 198	970 × 315 × 235	1100 × 330 × 235	1100 × 330 × 235	1100 × 330 × 235	
	Packing (WxHxD)	111111	920×370×282	1045 × 385 × 320	1180 × 400 × 320	1180 × 400 × 320	1180 × 400 × 320	
	Net / Gross Weight	kg	9/11	12/14	14 / 17	14 / 17	14 / 17	
Operating Range	Cooling	°C			> 17°C			
	Heating	C	<27°C					
Standard Controller		Model	Wireless Remote Control					
Sound Power Level		dB(A)	59	61	63	64	66	
Sound Pressure Level @ 1m		GD(/t)	50	53	54	55	59	
Dimensions	Dimension (W x D x H)	mm	768 × 311 × 545	837 × 353 × 545	930×388×700	930×388×700	1010 x 430 × 803	
	Packing (WxDxH)		850 × 365 × 605	920 × 395 × 605	1020 × 430 × 755	1020 × 430 × 755	1105 × 495 × 890	
	Net / Gross Weight	kg	27/31	30/34	47 / 51	47/53	61/65	
Refrigerant		Type			R32			
Refrigerant Piping	Charged Volume	kg	0.8	1.0	1.35	1.35	1.6	
	Pipe Size: Liquid / Gas	mm	Ф6.35 / Ф9.52	Φ6.35 / Φ12.7	Ф6.35 / Ф15.88	Ф6.35 / Ф15.88	Φ6.35 / Φ15.88	
	Maximum Pipe Length		20	20	30	30	30	
	Chargeless Length	m	10	10	10	10	10	
	Extra Charge for Lengths >5m	g/m	15	15	15	15	30	
	Maximum Vertical Separation	m	12	12	20	20	20	
Ambient	Cooling				-15 ~ 52°C			
Temperature Limits	Heating	°C			-15~24°C			
,	ricating				-10 - 24 0			

Capacities tested in accordance with AS/NZS 3823.2, with 5m interconnecting pipe length. With our policy of continuous improvement, we reserve the right to change, or discontinue at any time, specifications or designs without notice.

Note: All images contained within this brochure are for illustrative purposes only, the colours and finishes of the products featured are as close to the respective product range as photographic lighting and printing processes allow.

### Rinnai Australia Pty Ltd

ABN 74 005 138 769

100 Atlantic Drive, Keysborough, Victoria 3173

For further information call 1300 555 545 or visit rinnai.com.au

### TOTAL HOME COMFORT





